

COMPANY:	ORDER	QUOTE	Viewed Outside	Page No: of
TEL:	FAX:	Order Date: / /	ENERGY RATING 'A'	
EMAIL:	Req'd Date: / /	ENERGY RATING 'B'		
REF:	Signed:.....			If you do not choose a rating standard 'C' will apply with SILVER ALUMINIUM spacer

Window Colour:	WHITE	OAK	ROSEWOOD	OAK ON WHITE	ROSEWOOD ON WHITE	WHITE FOIL	CREAM FOIL	Special Foil or RAL Window Colours :			
Hardware Colour:	WHITE	GOLD	CHROME	BLACK	SATIN CHROME						
Spacer Bar Colour:	SILVER	GOLD	DARK BRONZE		WHITE	WARMEDEGE BLACK	WARMEDEGE GREY	WARMEDEGE WHITE			

SPECTUS WELDED VERTICAL SLIDING SASH SPEC/INFO **SIZES TO INCLUDE ALL CILLS AND ADD-ON**

Please circle your choices				Quantity:				Please indicate clearly any Add-on and Geogian bar detail				
Location:									Width			
Sash Horns (No horns unless stated)		<i>Mock Horns</i>		<i>Run Through (milled)</i>					Height			
Bottom Sash Rail (Small welded rail unless stated as standard)		<i>SMALL RAIL (welded)</i>		<i>DEEP RAIL (milled)</i>					Top Glass Type			
VS CILL (Stub cill unless stated as standard)		<i>STUB CILL (150)</i>		<i>PROJECT CILL (210)</i>					<i>Toughened</i>		<i>Obscure</i>	
VS Cam Locks (1 lock under 799mm - 2 locks 800mm and over)		<i>ONE (1)</i>		<i>TWO (2)</i>		<i>NONE</i>			Bottom Glass Type			
Travel Restrictor (limit stop) (No restrictor unless stated)		<i>ONE (1)</i>		<i>TWO (2)</i>		<i>NONE</i>			<i>Toughened</i>		<i>Obscure</i>	
Sash Tilt Rest Arms (Bottom only unless stated as standard)		<i>Bottom Sash (standard)</i>		<i>Top Sash & Bottom Sash</i>		<i>NONE</i>			Geogian Bar			
Trickle Vent (If required fitted to head of top sash)		<i>YES</i>		<i>NO</i>					<i>Internal (18mm)</i>		<i>Astargal (22mm)</i>	
Notes 1:									Notes 2:			

SPECTUS WELDED VERTICAL SLIDING SASH SPEC/INFO **SIZES TO INCLUDE ALL CILLS AND ADD-ON**

Please circle your choices				Quantity:				Please indicate clearly any Add-on and Geogian bar detail				
Location:									Width			
Sash Horns (No horns unless stated)		<i>Mock Horns</i>		<i>Run Through (milled)</i>					Height			
Bottom Sash Rail (Small welded rail unless stated as standard)		<i>SMALL RAIL (welded)</i>		<i>DEEP RAIL (milled)</i>					Top Glass Type			
VS CILL (Stub cill unless stated as standard)		<i>STUB CILL (150)</i>		<i>PROJECT CILL (210)</i>					<i>Toughened</i>		<i>Obscure</i>	
VS Cam Locks (1 lock under 799mm - 2 locks 800mm and over)		<i>ONE (1)</i>		<i>TWO (2)</i>		<i>NONE</i>			Bottom Glass Type			
Travel Restrictor (limit stop) (No restrictor unless stated)		<i>ONE (1)</i>		<i>TWO (2)</i>		<i>NONE</i>			<i>Toughened</i>		<i>Obscure</i>	
Sash Tilt Rest Arms (Bottom only unless stated as standard)		<i>Bottom Sash (standard)</i>		<i>Top Sash & Bottom Sash</i>		<i>NONE</i>			Geogian Bar			
Trickle Vent (If required fitted to head of top sash)		<i>YES</i>		<i>NO</i>					<i>Internal (18mm)</i>		<i>Astargal (22mm)</i>	
Notes 1:									Notes 2:			

SPECTUS WELDED VERTICAL SLIDING SASH SPEC/INFO **SIZES TO INCLUDE ALL CILLS AND ADD-ON**

Please circle your choices				Quantity:				Please indicate clearly any Add-on and Geogian bar detail				
Location:									Width			
Sash Horns (No horns unless stated)		<i>Mock Horns</i>		<i>Run Through (milled)</i>					Height			
Bottom Sash Rail (Small welded rail unless stated as standard)		<i>SMALL RAIL (welded)</i>		<i>DEEP RAIL (milled)</i>					Top Glass Type			
VS CILL (Stub cill unless stated as standard)		<i>STUB CILL (150)</i>		<i>PROJECT CILL (210)</i>					<i>Toughened</i>		<i>Obscure</i>	
VS Cam Locks (1 lock under 799mm - 2 locks 800mm and over)		<i>ONE (1)</i>		<i>TWO (2)</i>		<i>NONE</i>			Bottom Glass Type			
Travel Restrictor (limit stop) (No restrictor unless stated)		<i>ONE (1)</i>		<i>TWO (2)</i>		<i>NONE</i>			<i>Toughened</i>		<i>Obscure</i>	
Sash Tilt Rest Arms (Bottom only unless stated as standard)		<i>Bottom Sash (standard)</i>		<i>Top Sash & Bottom Sash</i>		<i>NONE</i>			Geogian Bar			
Trickle Vent (If required fitted to head of top sash)		<i>YES</i>		<i>NO</i>					<i>Internal (18mm)</i>		<i>Astargal (22mm)</i>	
Notes 1:									Notes 2:			



The SPECTUS Welded Vertical Slider

COMPANY:	ORDER	QUOTE	Viewed Outside	Page No: of
TEL:	FAX:	Order Date: / /	ENERGY RATING 'A'	
EMAIL:	Req'd Date: / /	ENERGY RATING 'B'		
REF:	Signed:.....	If you do not choose a rating standard 'C' will apply with SILVER ALUMINIUM spacer		

SPECTUS VS MULTI-SEGMENT DETAIL SHEET

Window Colour:	WHITE	OAK	ROSEWOOD	OAK ON WHITE	ROSEWOOD ON WHITE	WHITE FOIL	CREAM FOIL	Special Foil or RAL Window Colours :			
Hardware Colour:	WHITE	GOLD	CHROME	BLACK	SATIN CHROME						
Spacer Bar Colour:	SILVER	GOLD	DARK BRONZE		WHITE	WARMEDGE BLACK	WARMEDGE GREY	WARMEDGE WHITE			

SPECTUS WELDED VERTICAL SLIDING SASH SPEC/INFO

SIZES TO INCLUDE ALL CILLS AND ADD-ON

Please circle your choices		Quantity:		Please indicate clearly any Add-on and Georgian bar detail					
Location:									
Sash Horns (No horns unless stated)	Mock Horns	Run Through (milled)							
Bottom Sash Rail (Small welded rail unless stated as standard)	SMALL RAIL (welded)	DEEP RAIL (milled)							
VS CILL (Stub cill unless stated as standard)	STUB CILL (150)	PROJECT CILL (210)							
VS Cam Locks (1 lock under 799mm - 2 locks 800mm and over)	ONE (1)	TWO (2)	NONE						
Travel Restrictor (limit stop) (No restrictor unless stated)	ONE (1)	TWO (2)	NONE						
Sash Tilt Rest Arms (Bottom only unless stated as standard)	Bottom Sash (standard)	Top Sash & Bottom Sash	NONE						
Trickle Vent (If required fitted to head of top sash)	YES	NO							
Notes:				Top Glass Type		Bottom Glass Type		Georgian Bar	
				Toughened	Obscure	Toughened	Obscure	Internal (18mm)	Astargal (22mm)

SPECTUS WELDED VERTICAL SLIDING SASH SPEC/INFO

SIZES TO INCLUDE ALL CILLS AND ADD-ON

Please circle your choices		Quantity:		Please indicate clearly any Add-on and Georgian bar detail					
Location:									
Sash Horns (No horns unless stated)	Mock Horns	Run Through (milled)							
Bottom Sash Rail (Small welded rail unless stated as standard)	SMALL RAIL (welded)	DEEP RAIL (milled)							
VS CILL (Stub cill unless stated as standard)	STUB CILL (150)	PROJECT CILL (210)							
VS Cam Locks (1 lock under 799mm - 2 locks 800mm and over)	ONE (1)	TWO (2)	NONE						
Travel Restrictor (limit stop) (No restrictor unless stated)	ONE (1)	TWO (2)	NONE						
Sash Tilt Rest Arms (Bottom only unless stated as standard)	Bottom Sash (standard)	Top Sash & Bottom Sash	NONE						
Trickle Vent (If required fitted to head of top sash)	YES	NO							
Notes:				Top Glass Type		Bottom Glass Type		Georgian Bar	
				Toughened	Obscure	Toughened	Obscure	Internal (18mm)	Astargal (22mm)

SPECTUS WELDED VERTICAL SLIDING SASH SPEC/INFO

SIZES TO INCLUDE ALL CILLS AND ADD-ON

Please circle your choices		Quantity:		Please indicate clearly any Add-on and Georgian bar detail					
Location:									
Sash Horns (No horns unless stated)	Mock Horns	Run Through (milled)							
Bottom Sash Rail (Small welded rail unless stated as standard)	SMALL RAIL (welded)	DEEP RAIL (milled)							
VS CILL (Stub cill unless stated as standard)	STUB CILL (150)	PROJECT CILL (210)							
VS Cam Locks (1 lock under 799mm - 2 locks 800mm and over)	ONE (1)	TWO (2)	NONE						
Travel Restrictor (limit stop) (No restrictor unless stated)	ONE (1)	TWO (2)	NONE						
Sash Tilt Rest Arms (Bottom only unless stated as standard)	Bottom Sash (standard)	Top Sash & Bottom Sash	NONE						
Trickle Vent (If required fitted to head of top sash)	YES	NO							
Notes:				Top Glass Type		Bottom Glass Type		Georgian Bar	
				Toughened	Obscure	Toughened	Obscure	Internal (18mm)	Astargal (22mm)

Bison Frames (UK) Ltd. Unit H1, Bromcliffe Park, Monk Bretton, Barnsley. S71 5RN.

Tel: 01226 715250

Fax: 01226 707947

Email: sales@bisonframes.co.uk

Website: www.bisonframes.co.uk



The SPECTUS Welded Vertical Slider

COMPANY:		ORDER	QUOTE	Viewed Outside	Page No: of
TEL:	FAX:	Order Date: / /			ENERGY RATING 'A'
EMAIL:		Req'd Date: / /			ENERGY RATING 'B'
REF:		Signed:.....			If you do not choose a rating standard 'C' will apply with SILVER ALUMINIUM spacer

SPECTUS VS BAY WELDED CILL DETAIL SHEET

Window Colour:	WHITE	OAK	ROSEWOOD	OAK ON WHITE	ROSEWOOD ON WHITE	WHITE FOIL	CREAM FOIL	Special Foil or RAL Window Colours :		
Hardware Colour:	WHITE	GOLD	CHROME	BLACK	SATIN CHROME					
Spacer Bar Colour:	SILVER	GOLD	DARK BRONZE		WHITE	WARMEDGE BLACK	WARMEDGE GREY	WARMEDGE WHITE		

SPECTUS WELDED VERTICAL SLIDING SASH SPEC/INFO

SIZES TO INCLUDE ALL CILLS AND ADD-ON

Please circle your choices		Quantity:	
Location:			
Sash Horns (No horns unless stated)	Mock Horns	Run Through (milled)	
Bottom Sash Rail (Small welded rail unless stated as standard)	SMALL RAIL (welded)	DEEP RAIL (milled)	
VS CILL (Stub cill unless stated as standard)	STUB CILL (150)	PROJECT CILL (210)	
VS Cam Locks (1 lock under 799mm - 2 locks 800mm and over)	ONE (1)	TWO (2)	NONE
Travel Restrictor (limit stop) (No restrictor unless stated)	ONE (1)	TWO (2)	NONE
Sash Tilt Rest Arms (Bottom only unless stated as standard)	Bottom Sash (standard)	Top Sash & Bottom Sash	NONE
Trickle Vent (If required fitted to head of top sash)	YES	NO	
Notes:			

Please indicate clearly any Add-on and Georgian bar detail														
A Left Side	B Front	C Right Side												
↑	↑	↑												
↓	↓	↓												
Split														
<table border="1"> <tr> <td colspan="2">Top Glass Type</td> <td colspan="2">Bottom Glass Type</td> <td colspan="2">Georgian Bar</td> </tr> <tr> <td>Toughened</td> <td>Obscure</td> <td>Toughened</td> <td>Obscure</td> <td>Internal (18mm)</td> <td>Astargal (22mm)</td> </tr> </table>			Top Glass Type		Bottom Glass Type		Georgian Bar		Toughened	Obscure	Toughened	Obscure	Internal (18mm)	Astargal (22mm)
Top Glass Type		Bottom Glass Type		Georgian Bar										
Toughened	Obscure	Toughened	Obscure	Internal (18mm)	Astargal (22mm)									

INTERNAL CILL SIZES, OVERALL HEIGHT & ANGLES

DRAW CILL PLAN BELOW

Left side 'A' internal cill size
Front 'B' internal cill size
Right side 'C' internal cill size
Overall Height
Left Angle (Variable angle VS bay post 120 to 150 degrees only)
Right Angle (Variable angle VS bay post 120 to 150 degrees only)

<p>90 DEGREE FIXED ANGLE VS BAY POST ALSO AVAILABLE</p> <p>IF YOU DO NOT REQUIRE A WELDED CILL & BAY POSTS USE THE SINGLE VS OR MULTI-SEGMENT FORMS WHEN ORDERING</p>

NOTES:

ALL BAYS ARE PRE ASSEMBLED AND READY TO FIT. THE CILL WILL BE 300mm LONGER AT EACH SIDE.